RED “N” TACKY® Spray Grease

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)
Issue date: 3/4/2025 Revision date: 7/16/2026 Supersedes: 7/7/2026 Version: 4.0

SECTION 1 Identification

1.1. Product identifier

Product form	:	Mixture
Product name	:	RED “N” TACKY® Spray Grease
Part Number	:	11025
Vaporizer	:	Aerosol

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture	:	lubricants

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number	:	For Chemical Emergency Call ChemTel 24hr/day 7days/week. Within USA, Canada, Puerto Rico & US Virgin Islands: 1-800-255-3924. International: 1-813-248-0585 (collect calls accepted). Australia: 1-300-954-583. Brazil: 0-800-591-6042. China: 400-120-0751. India: 000-800-100-4086. Mexico: 800-099-0731.

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Aerosol, Category 1	H222;H229	Extremely flammable aerosol. Pressurized container; may burst if heated.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412	Harmful to aquatic life with long lasting effects.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :

Signal word (GHS US) : Danger

Hazard statements (GHS US)	:	H222 - Extremely flammable aerosol H229 - Pressurized container; may burst if heated H304 - May be fatal if swallowed and enters airways H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness H361 - Suspected of damaging fertility or the unborn child H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (GHS US)	:	P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing dust, fume, gas, mist, vapors, spray. P264 - Wash hands, forearms and face thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing must not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection. P301+P310 - If swallowed: Immediately call a poison center or doctor. P302+P352 - IF ON SKIN: Wash with plenty of water. P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - If exposed or concerned: Get medical advice/attention. P312 - Call a poison center or doctor if you feel unwell. P331 - Do NOT induce vomiting. P333+P313 - If skin irritation or rash occurs: Get medical advice or attention. P337+P313 - If eye irritation persists: Get medical advice or attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C). P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Acetic acid, methyl ester	CAS-No.: 79-20-9	15 - 40*	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
2-Methylpentane	CAS-No.: 107-83-5	10 - 30*	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Propane	CAS-No.: 74-98-6	5 - 10*	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	CAS-No.: 68584-23-6	1 - 5*	Skin Sens. 1B, H317
Butane	CAS-No.: 106-97-8	3 - 7*	Flam. Gas 1, H220 Press. Gas (Comp.), H280
Pentane	CAS-No.: 109-66-0	1 - 5*	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Sulfonic acids, petroleum, calcium salts	CAS-No.: 61789-86-4	0.5 - 1.5*	Skin Sens. 1B, H317
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	1 - 5*	Asp. Tox. 1, H304 Aquatic Chronic 4, H413
Hexane	CAS-No.: 110-54-3	0.1 - 1*	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	CAS-No.: 70024-69-0	0.5 - 1.5*	Skin Sens. 1, H317
Benzenamine, ar-nonyl-N-(nonylphenyl)-	CAS-No.: 36878-20-3	0.1 - 1*	Repr. 2, H361 Aquatic Chronic 4, H413
1,3,4-Thiadiazole-2(3H)-thione, 5,5'-dithiobis-	CAS-No.: 72676-55-2	0.1 - 1*	Skin Sens. 1, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret
Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.
Personal protection for first-aid responders. : First-aiders should consider self-protection and use the recommended personal protective equipment (see section 8).

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after inhalation : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : May cause eye irritation. Eye irritation.
Symptoms/effects after ingestion : May cause irritation to the digestive tract. Risk of lung edema.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS THE LEAK CAN BE STOPPED. Dry chemical, CO2, or water spray or regular foam. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol. Pressurized container: may burst if heated. Heating may cause a fire or explosion.
Explosion hazard : Explosion risk in case of fire. Heating may cause an explosion.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Precautionary measures fire : Keep container tightly closed and away from heat, sparks and flame.
Firefighting instructions : Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.
Environmental precautions : Avoid release to the environment. Avoid discharge to atmosphere.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Use only outdoors or in a well-ventilated area. Prevent the build-up of electrostatic charge. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Use only non-sparking tools. Ground/bond container and receiving equipment.

Storage conditions : Keep only in original container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in fireproof place. Keep container closed when not in use. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Keep container tightly closed.

Packaging materials : Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Propane (74-98-6)	
USA - ACGIH® - Threshold Limit Values	
Local name	Propane
Remark (ACGIH®)	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Propane
OSHA PEL TWA	1800 mg/m³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Propane
Cal/OSHA PEL (OEL TWA)	1800 mg/m³
	1000 ppm

Propane (74-98-6)	
Remark (Cal/OSHA)	(h) A number of gases and vapors, when present in high concentrations, act primarily as asphyxiants without other adverse effects. A concentration limit is not included for each material because the limiting factor is the available oxygen. (Several of these materials present fire or explosion hazards.)
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Propane
NIOSH REL 10h TWA	1000 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

Butane (106-97-8)	
USA - ACGIH® - Threshold Limit Values	
Local name	Butane
ACGIH® TLV® STEL	1000 ppm
Remark (ACGIH®)	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2024
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Butane
Cal/OSHA PEL (OEL TWA)	1900 mg/m³
	800 ppm
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)

Acetic acid, methyl ester (79-20-9)	
USA - ACGIH® - Threshold Limit Values	
Local name	Methyl acetate
ACGIH® TLV® TWA	200 ppm
ACGIH® TLV® STEL	250 ppm
Remark (ACGIH®)	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Methyl acetate
OSHA PEL TWA	610 mg/m³
	200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Methyl acetate
Cal/OSHA PEL (OEL TWA)	610 mg/m³
	200 ppm

Acetic acid, methyl ester (79-20-9)	
Cal/OSHA STEL	760 mg/m³
	250 ppm
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Methyl acetate
NIOSH REL 10h TWA	200 ppm
NIOSH REL STEL	250 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

2-Methylpentane (107-83-5)	
USA - ACGIH® - Threshold Limit Values	
Local name	2-Methyl pentane
ACGIH® TLV® TWA	200 ppm
Remark (ACGIH®)	TLV® Basis: URT irr; lung dam. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

Pentane (109-66-0)	
USA - ACGIH® - Threshold Limit Values	
Local name	Pentane
ACGIH® TLV® TWA	2950 mg/m³
	1000 ppm
Remark (ACGIH®)	TLV® Basis: Narcosis; resp tract irr
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Pentane
OSHA PEL TWA	2950 mg/m³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Pentane
Cal/OSHA PEL (OEL TWA)	1800 mg/m³
	600 ppm
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Pentane
NIOSH REL 10h TWA	120 ppm
NIOSH REL C	610 ppm [15-min]

Pentane (109-66-0)	
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

Hexane (110-54-3)	
USA - ACGIH® - Threshold Limit Values	
Local name	n-Hexane
ACGIH® TLV® TWA	176 mg/m³
	50 ppm
Remark (ACGIH®)	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
USA - ACGIH® - Biological Exposure Indices	
Local name	n-Hexane
BEI	0.5 mg/l Parameter: 2,5-Hexanedione - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	n-Hexane
OSHA PEL TWA	1800 mg/m³
	500 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	n-Hexane
Cal/OSHA PEL (OEL TWA)	180 mg/m³
	50 ppm
Remark (Cal/OSHA)	S - Skin notation and Protecting Clothing
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	n-Hexane
NIOSH REL 10h TWA	50 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:
Wear recommended personal protective equipment.

Hand protection:
Protective gloves

Eye protection:
Safety glasses

Skin and body protection:
Wear suitable protective clothing

Respiratory protection:
Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. [In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	:	Liquid
Color	:	Colorless
Odor	:	petroleum-like odor
Odor threshold	:	No data available
pH	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	-104 °C (Propane)
Flammability (solid, gas)	:	Not applicable.
Vapor pressure	:	95000 Pa (Propane) @ 20 ° C
Relative vapor density at 20°C	:	No data available
Relative density	:	No data available
Density	:	1.56 @ 0 ° C (Propane)
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Auto-ignition temperature	:	450 °C (Propane)
Decomposition temperature	:	No data available
Viscosity, kinematic	:	< 20.5 mm²/s @ 40 ° C
Explosion limits	:	Lower explosion limit: 2.1 Vol-% (Propane) Upper explosion limit: 9.5 Vol-% (Propane)
Particle characteristics	:	No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

Gas group	:	Press. Gas (Liq.)

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Extremely flammable aerosol. Pressurized container: may burst if heated.

10.3. Possibility of hazardous reactions

May mass explode in fire. Heating may cause a fire or explosion.

10.4. Conditions to avoid

High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Combustible materials.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
LD50 oral rat	> 16000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: other:
LD50 dermal rabbit	> 4000 mg/kg body weight Animal: rabbit, Guideline: other:

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
LD50 oral rat	> 16000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: other:
LD50 dermal rat	> 2000 mg/kg Source: International Uniform ChemicaL Information Database
LD50 dermal rabbit	> 4000 mg/kg body weight Animal: rabbit, Guideline: other:
LC50 Inhalation - Rat	> 1.9 mg/l air Animal: rat, Guideline: EPA OPP 81-3 (Acute inhalation toxicity)

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0)	
LD50 oral rat	> 16000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: other:
LD50 dermal rabbit	> 4000 mg/kg body weight Animal: rabbit, Guideline: other:
LC50 Inhalation - Rat	> 1.9 mg/l air Animal: rat, Guideline: EPA OPP 81-3 (Acute inhalation toxicity)
LC50 Inhalation - Rat (Dust/Mist)	> 1.9 mg/l Source: ECHA

Propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))

Butane (106-97-8)	
LC50 Inhalation - Rat [ppm]	276798.8 ppm

Acetic acid, methyl ester (79-20-9)	
LD50 oral rat	6482 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 oral	6482 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LD50 dermal	5000 mg/kg
ATE US (oral)	6482 mg/kg body weight
ATE US (dermal)	5000 mg/kg body weight

2-Methylpentane (107-83-5)	
LD50 oral rat	≈ 15.84 mg/kg body weight Animal: rat
LC50 Inhalation - Rat (Vapors)	> 20 mg/l

Pentane (109-66-0)	
LD50 oral rat	> 2000 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 oral	2500 mg/kg
LD50 dermal	3000 mg/kg
LC50 Inhalation - Rat	> 20 mg/l air (4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Vapors)	364 mg/l Source: ChemIDplus
ATE US (oral)	2500 mg/kg body weight
ATE US (dermal)	3000 mg/kg body weight
ATE US (vapors)	364 mg/l/4h

Hexane (110-54-3)	
LD50 oral rat	16000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 oral	15800 mg/kg
LD50 dermal rabbit	> 3350 mg/kg body weight (Equivalent or similar to OECD 402, 4 h, Rabbit, Male, Read-across, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 17.6 mg/l air (Equivalent or similar to OECD 403, 24 h, Rat, Male, Experimental value, Inhalation (vapours), 30 day(s))
LC50 Inhalation - Rat (Vapors)	259.354 mg/l Source: ECHA

1,3,4-Thiadiazole-2(3H)-thione, 5,5'-dithiobis- (72676-55-2)	
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: other:

Skin corrosion/irritation : Causes skin irritation.

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
pH	8

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0)	
pH	8.1 Source: ECHA Chem

Propane (74-98-6)	
pH	No data available in the literature

Acetic acid, methyl ester (79-20-9)	
pH	No data available in the literature

2-Methylpentane (107-83-5)	
pH	No data available in the literature

Pentane (109-66-0)	
pH	No data available in the literature

Hexane (110-54-3)	
pH	7 (< 0.01 %, 25 °C)

Serious eye damage/irritation : Causes serious eye irritation.

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
pH	8

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0)	
pH	8.1 Source: ECHA Chem

Propane (74-98-6)	
pH	No data available in the literature

Acetic acid, methyl ester (79-20-9)	
pH	No data available in the literature

2-Methylpentane (107-83-5)	
pH	No data available in the literature

Pentane (109-66-0)	
pH	No data available in the literature

Hexane (110-54-3)	
pH	7 (< 0.01 %, 25 °C)

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Acetic acid, methyl ester (79-20-9)	
LOAEL (animal/male, F0/P)	1000 mg/kg body weight Animal: mouse, Animal sex: male, Guideline: other:

Pentane (109-66-0)	
NOAEL (animal/male, F0/P)	300 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]
NOAEL (animal/female, F0/P)	≥ 1000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]

STOT-single exposure : May cause drowsiness or dizziness.

Acetic acid, methyl ester (79-20-9)	
STOT-single exposure	May cause drowsiness or dizziness.

2-Methylpentane (107-83-5)	
STOT-single exposure	May cause drowsiness or dizziness.

Pentane (109-66-0)	
STOT-single exposure	May cause drowsiness or dizziness.

Hexane (110-54-3)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
NOAEL (oral,rat,90 days)	500 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	> 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
NOAEL (oral,rat,90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	> 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation,rat,dust/mist/fume,90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0)	
NOAEL (oral,rat,90 days)	500 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	> 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Acetic acid, methyl ester (79-20-9)	
NOAEC (inhalation, rat, 28 days)	6.66 mg/l
NOAEC (inhalation, rat, 90 days)	1.06 mg/l

Pentane (109-66-0)	
NOAEC (inhalation,rat,vapor,90 days)	30 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Guideline: other:, Guideline: EPA OTS 798.2450 (90-Day Inhalation Toxicity), Guideline: other:, Guideline: other:

Hexane (110-54-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

RED “N” TACKY® Spray Grease	
Vaporizer	Aerosol
Viscosity, kinematic	< 20.5 mm²/s @ 40 ° C

RED “N” TACKY® Spray Grease	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Viscosity, kinematic	18 mm²/s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes
Propane (74-98-6)	
Viscosity, kinematic	No data available in the literature
Acetic acid, methyl ester (79-20-9)	
Viscosity, kinematic	No data available in the literature
2-Methylpentane (107-83-5)	
Viscosity, kinematic	0.47 mm²/s (20 °C, Calculated)
Pentane (109-66-0)	
Viscosity, kinematic	0.2 – 0.52 mm²/s (20 °C, ASTM D7042: Dynamic viscosity and density of liquids)
Hexane (110-54-3)	
Viscosity, kinematic	No data available in the literature

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after inhalation : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : May cause eye irritation. Eye irritation.
Symptoms/effects after ingestion : May cause irritation to the digestive tract. Risk of lung edema.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short–term (acute) : Not classified
Hazardous to the aquatic environment, long–term (chronic) : Harmful to aquatic life with long lasting effects.

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
LC50 - Fish [1]	10000 mg/l Source: ECHA
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
EC50 - Crustacea [1]	> 1000 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
LC50 - Fish [1]	> 0.0013 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0)	
LC50 - Fish [1]	> 10000 mg/l Source: ECHA
EC50 - Crustacea [1]	> 1000 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

Propane (74-98-6)	
LC50 - Fish [1]	50 mg/l (96 h, Pisces, Fresh water, QSAR, Estimated value)
EC50 96h - Algae [1]	12 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)

Butane (106-97-8)	
LC50 - Fish [1]	27.98 mg/l Source: QSAR
EC50 96h - Algae [1]	16.47 mg/l Source: QSAR

Acetic acid, methyl ester (79-20-9)	
LC50 - Fish [1]	250 – 350 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	1027 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 72h - Algae [1]	> 120 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
ErC50 algae	> 120 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)

2-Methylpentane (107-83-5)	
LC50 - Fish [1]	1.478 mg/l (96 h, Pimephales promelas, QSAR)
EC50 96h - Algae [1]	4.321 mg/l (US EPA, Algae, Calculated value)

Pentane (109-66-0)	
LC50 - Fish [1]	4.3 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	2.7 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value)
ErC50 algae	11 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Selenastrum capricornutum, Static system, Fresh water, Experimental value, GLP)
NOEC chronic algae	2 mg/l

Hexane (110-54-3)	
LC50 - Fish [1]	2.5 mg/l
EC50 - Crustacea [1]	3.9 mg/l

1,3,4-Thiadiazole-2(3H)-thione, 5,5'-dithiobis- (72676-55-2)	
EC50 - Crustacea [1]	3 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	20 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

RED “N” TACKY® Spray Grease	
Persistence and degradability	Not rapidly degradable

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
Persistence and degradability	Not rapidly degradable

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
Persistence and degradability	Not rapidly degradable

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
Persistence and degradability	Not rapidly degradable

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0)	
Persistence and degradability	Not rapidly degradable

Propane (74-98-6)	
Persistence and degradability	Readily biodegradable in water.

Butane (106-97-8)	
Persistence and degradability	Not rapidly degradable

Acetic acid, methyl ester (79-20-9)	
Persistence and degradability	Readily biodegradable in water.

2-Methylpentane (107-83-5)	
Persistence and degradability	Readily biodegradable in water.

Pentane (109-66-0)	
Persistence and degradability	Readily biodegradable in water.

Hexane (110-54-3)	
Persistence and degradability	Biodegradable in the soil, Readily biodegradable in water.
ThOD	3.52 g O_2/g substance

1,3,4-Thiadiazole-2(3H)-thione, 5,5'-dithiobis- (72676-55-2)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
Partition coefficient n-octanol/water (Log Pow)	> 4.46 Source: ECHA

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0)	
Partition coefficient n-octanol/water (Log Pow)	> 5.47 Source: ECHA

Propane (74-98-6)	
Partition coefficient n-octanol/water (Log Pow)	1.1 – 2.8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Butane (106-97-8)	
Partition coefficient n-octanol/water (Log Pow)	2.89 Source: ICSC

Acetic acid, methyl ester (79-20-9)	
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

2-Methylpentane (107-83-5)	
BCF - Fish [1]	356 (Pisces, Literature study, QSAR)
Partition coefficient n-octanol/water (Log Pow)	3.214 (Calculated, KOWWIN, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Pentane (109-66-0)	
Partition coefficient n-octanol/water (Log Pow)	3.5 (Experimental value, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Hexane (110-54-3)	
Partition coefficient n-octanol/water (Log Pow)	4 (Experimental value, Equivalent or similar to OECD 107, 20 °C)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
Mobility in soil	35900000 Source: EPISUITE

Propane (74-98-6)	
Surface tension	No data available in the literature
Ecology - soil	Not applicable (gas).

Acetic acid, methyl ester (79-20-9)	
Surface tension	24 mN/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)

Acetic acid, methyl ester (79-20-9)	
Ecology - soil	Highly mobile in soil.

2-Methylpentane (107-83-5)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.044 – 2.786 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

Pentane (109-66-0)	
Surface tension	15.49 mN/m (25 °C, 100 %)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.9 (log Koc, QSAR)
Ecology - soil	Low potential for adsorption in soil.

Hexane (110-54-3)	
Surface tension	17.89 mN/m (25 °C, 1 g/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.34 (log Koc, QSAR)
Ecology - soil	Low potential for mobility in soil.

1,3,4-Thiadiazole-2(3H)-thione, 5,5'-dithiobis- (72676-55-2)	
Mobility in soil	518.5 Source: EPISUITE

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector’s sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Do not re-use empty containers.
Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN1950	UN1950	UN1950	UN1950
14.2. Proper Shipping Name			
Aerosols	AEROSOLS	AEROSOLS	Aerosols, flammable

DOT	TDG	IMDG	IATA
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No. (DOT) : UN1950
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
DOT Vessel Stowage Location : A - The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow ‘‘separated from’’ Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

TDG

UN-No. (TDG) : UN1950
TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment),107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.
(2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L
Emergency Response Guide (ERG) Number : 126

IMDG

Special provision (IMDG) : 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG) : SP277

Excepted quantities (IMDG)	:	E0
Packing instructions (IMDG)	:	P207, LP200
Packing provisions (IMDG)	:	PP87, L2
EmS-No. (Fire)	:	F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	:	S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	:	None
Stowage and handling (IMDG)	:	SW1, SW22
Segregation (IMDG)	:	SG69

IATA

Special provision (IATA)	:	A145, A167, A802
PCA Excepted quantities (IATA)	:	E0
PCA Limited quantities (IATA)	:	Y203
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	203
PCA max net quantity (IATA)	:	75kg
CAO packing instructions (IATA)	:	203
CAO max net quantity (IATA)	:	150kg
ERG code (IATA)	:	10L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Hexane	CAS-No. 110-54-3	0.1 - 1*%

Hexane (110-54-3)

Listed on EPA Hazardous Air Pollutant (HAPS)
Listed on EPA HAPs Acute Dose Response Assessment List – Exposure limits

CERCLA RQ	5000 lb

15.2. International regulations

CANADA

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)

Listed on the Canadian DSL (Domestic Substances List)

Sulfonic acids, petroleum, calcium salts (61789-86-4)

Listed on the Canadian DSL (Domestic Substances List)

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0)

Listed on the Canadian DSL (Domestic Substances List)

Propane (74-98-6)

Listed on the Canadian DSL (Domestic Substances List)

Butane (106-97-8)

Listed on the Canadian DSL (Domestic Substances List)

Acetic acid, methyl ester (79-20-9)

Listed on the Canadian DSL (Domestic Substances List)

2-Methylpentane (107-83-5)

Listed on the Canadian DSL (Domestic Substances List)

Pentane (109-66-0)

Listed on the Canadian DSL (Domestic Substances List)

Hexane (110-54-3)

Listed on the Canadian DSL (Domestic Substances List)

1,3,4-Thiadiazole-2(3H)-thione, 5,5'-dithiobis- (72676-55-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Propane (74-98-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Butane (106-97-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Acetic acid, methyl ester (79-20-9)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

2-Methylpentane (107-83-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Pentane (109-66-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Hexane (110-54-3)

Listed on EPA HAPs Acute Dose Response Assessment List – Exposure limits
Listed on INSQ (Mexican National Inventory of Chemical Substances)

1,3,4-Thiadiazole-2(3H)-thione, 5,5'-dithiobis- (72676-55-2)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

WARNING: This product can expose you to chemicals including Naphthalene, which is known to the State of California to cause cancer, and n-Hexane, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)
Revision date : 7/16/2026
Issue date : 3/4/2025

Full text of hazard classes and H-statements	
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H229	Pressurized container; may burst if heated
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.